

Irish Robotics GPS/GSM TM/1 Antenna

Mounting Instructions

Step1 – Choosing a mounting location

The optimum position to mount the antenna is on the front windscreen. However, on the rear windscreen or discretely on or under a plastic dashboard are acceptable.

- For windscreen mounting, the recommended positions are in the top/bottom corners or the top centre, **not** across any demister wires.
- The antenna must be positioned at least 20mm from any metal surface.
- Suitable mounting surfaces are glass or non-metallic.

NOTE: Best results are with a vertical mounting (cable exit from top or bottom).

Step2 – Mounting

- The windscreen and antenna must be cleaned with the supplied surface cleaner and allowed to dry completely.
- Remove one side of the adhesive pad and firmly press onto the glass or non-metallic surface (no bubbles).
- Remove the other side of the adhesive pad and press the antenna firmly onto it – Note: The coloured dot must face towards the ‘sky’.

CAUTION

- a) Ensure the coloured dot is pointing outwards – to the sky.
- b) Ensure the glass is cleaned as stated.
- c) Ensure no condensation is on the glass if in cold conditions.
- d) Keep any oil, water and your hands off the mounting site and the antenna.
- e) Do not disturb within 24 hours of mounting – to allow full adhesion to take place.

After its use, this product must be processed as electronic scrap for proper disposal according to the prevailing waste disposal regulations of your community/district/state.

For any additional information or advice on mounting – contact Irish Robotics on +353 1 8499476 or mobile +353 872 144506